

# structo

WALL  
SYSTEMS



FITS PERFECTLY WITH GLASS  
WALLS

DECOR PROFILES CAN CREATE  
CONTRASTING LOOKS

## ALUSLIDE- 12

Maximum door height: **2600 mm\***

\* with 8mm glass and if width max 1000mm

Maximum door width: **1250 mm\***

\* with 8mm glass and if height max 2100mm

Suitable glasses with a  
thickness: **8 – 8,76 mm**



+372 666 5017



info@structo.ee



www.structo.ee

ALUSLIDE-12 is an aluminum framed sliding door (single or pair) for glasses between 8 - 8,76mm.

Door profile dimensions are 12x33mm.

The standard surface finish of aluminum profiles is natural (silver) anodizing, but it is also possible to order a painted surface according to the RAL colour catalogue.

Possible types of glass are tempered, laminated or tempered-laminated.


The surface of the glass can be bright, very bright, mass-tinted, background-painted or matte.

Aluminum decor profiles can be glued anywhere on the glass, which can give the door panel an exciting and contrasting look.

Standard lock case is ASSA 310, but it is possible to use different lock cases. Other hardware (cylinder and/or twist knob must be compatible with chosen lock case).

Standard handle is a built in sliding door handle (round 34/54mm), but it is also possible to use other handles.

The structures adjacent to the product must be strong enough to allow profiles to be attached to them.



Maximum door height:	<b>2600 mm*</b>
* with 8mm glass and if width max 1000mm	

Maximum door width:	<b>1250 mm*</b>
* with 8mm glass and if height max 2100mm	

Suitable glasses with a thickness:	<b>8 – 8,76 mm</b>
------------------------------------	--------------------



+372 666 5017



info@structo.ee




www.structo.ee

ALUSLIDE-

12


STANDARD SOLUTION




# ALUSLIDE-

# 12


## EXAMPLE SOLUTION WITH DECOR PROFILE




CONNECTION WITH CEILING




CONNECTION WITH UPPER OVERLIGHT



CONNECTION WITH FLOOR




DECOR PROFILES ARE GLUED ON BOTH SIDES OF THE GLASS




- - seal, EPDM-50Dha\_5mm\_BLACK
- g - glued connection
- ⊗ - seal, VS118/8 black, white, dark gray
- | - seal, FIX-SEAL/S 3x10mm, black


CONNECTION WITH WALL (WITH LOCKING AND/OR PULL HANDLES)



CONNECTION WITH WALL (BUILT-IN HANDLES AND WITHOUT LOCKING)




CONNECTION WITH CEILING




- - seal, EPDM-50Dha\_5mm\_BLACK
- g - glued connection
- ⊗ - seal, VS118/8 black, white, dark gray


CONNECTION WITH FLOOR



DECOR PROFILES ARE GLUED  
ON BOTH SIDES OF THE GLASS



CONNECTION WITH WALL (WITH LOCKING AND/OR PULL HANDLES)



CONNECTION WITH WALL (BUILT-IN HANDLES AND WITHOUT LOCKING)

