Structo WALL SYSTEMS



MINIMALIST SOLUTION
THAT FITS PERFECTLY
WITH PORTALS

DECOR PROFILES CAN
CREATE CONTRASTING
LOOKS

GLASSLINE-30

| Maximum wall height: | 3500 mm |
|---|-----------------------------------|
| Soundproofing: * with 55.2 more soundproof | $Rw = 37 dB^*$ of laminated glass |
| Dimensions of the profile (width x height): | 20 x 30 mm |
| Suitable glasses with a thickness: | 8 – 11,14 mm |







TECHNICAL DESCRIPTION



GLASSLINE-30 is a full glass wall system made with aluminum profiles for glasses between 8-11,14mm.

The width of the profile is 20mm and the height is 30mm.

The standard surface finish of aluminum profiles is natural (silver) anodizing but it is also possible to order a painted surface according to the RAL colour catalogue.

Possible types of glass are tempered, laminated or tempered-laminated.

The surface of the glass can be bright, very bright, mass-tinted, background-painted or matte.

Adjacent glass panes are joined together with silicone tape. If desired, the joint can be covered with a 30mmx2mm aluminum Decor profile. Decor profile can be glued anywhere on the glass surface to create exiting looks.

The standard floor profile height is 30mm, but it is also possible to choose a 70mm profile with the same width.


A 5mm black circular cross-section EPDM top seal is used as the glass seal. Additional seal is required for maximum soundproofing.

The structures adjacent to the product must be strong enough to allow profiles to be attached to them.

| Maximum wall height: | 3500 mm |
|---|--------------|
| Dimensions of the profile (width x height): | 20 x 30 mm |
| Suitable glasses with a thickness: | 8 – 11,14 mm |

Soundproofing measured in laboratory (Rw):

Rw = 33 dB(with 10mm glass) Rw = 37 dB(with 55.2 more soundproof laminated glass)








GLASSLINE-30_v2_02082021


STANDARD SOLUTION






SOLUTION WITH HIGH FLOOR PROFILE





EXAMPLE SOLUTION WITH DECOR PROFILE







CONNECTION UNITS




CONNECTION WITH CEILING




CONNECTION WITH WALL







CONNECTION WITH FLOOR



CONNECTION WITH SIDE GLASS



CONNECTION WITH **DECOR PROFILES**



- seal, EPDM-50Dha_5mm_BLACK


- g glued connection
 | seal, FIX-SEAL/S 3x10mm, black
 | AFTC double-sided tape, 2,5x5mm / 3x7mm / 3x10mm, colourless



CONNECTION UNITS WITH COMPATIBLE PRODUCTS




90° CONNECTION UNIT WITH PORTAL PORTA-92A OR ELZONE-92A




CONNECTION WITH PORTAL PORTA-92A



CONNECTION WITH PORTAL PORTA-53



CONNECTION WITH WALL ELZONE-92A



GLASSLINE-30_v2_02082021